



BLAGDON


B50 & X50

AIR OPERATED DOUBLE DIAPHRAGM PUMP

2" Non-Metallic '05' Series

B50


DIMENSIONS



General Assembly :- B50 Moulded Pump, All dimensions +/- 3mm

B50

PERFORMANCE



B50 Moulded Pump Performance Curve
Performance based on water at ambient temperature

FLUID CONNECTIONS	CAPACITY	MAX SOLIDS	MAX DISCHARGE HEAD	DISPLACEMENT/STROKE
2" ANSI 150 / DN50 Compatible Flange	0 - 500 Litres/Minute (0 - 110 Gallons/Minute)	6 MM (1/4")	88 Meters (289 ft)	1.9 Litres (0.42 UK Gallons)
MAX. WORKING PRESSURE	AIR INLET	TEMPERATURE LIMITS		PUMP WEIGHTS :-
8.6 Bar (125 psi)	3/4" BSP (F)	Polypropylene :- 70°C PVDF (Kynar) :- 90°C		PT/GT :- 38 Kg PW/GW :- 70 Kg KT :- 48 Kg KW :- 80 Kg

ⓘ Caution - Operating temperature limitations are as follows:

Operating Temperatures

Materials

Maximum

Minimum

Optimum

Buna-n - General purpose, oil resistant. Shows good solvent, oil, water and hydraulic fluid resistance. Should not be used with highly polar solvents like acetone and MEK, ozone, chlorinated hydrocarbons and nitro hydrocarbons.

176°F
80°C

-18°F
-28°C

50° to 140°F
10° to 60°C

EPDM - Shows very good water and chemical resistance. Has poor resistance to oils and solvents, but is fair on ketones and alcohols.

212°F
100°C

-11°F
-24°C

50° to 212°F
10° to 100°C

Neoprene - All purpose. Resistant to vegetable oil. Generally not affected by moderate chemicals, fats greases and many oils and solvents. Generally attacked by strong oxidising acids, ketones, esters, nitro hydro carbons and chlorinated aromatic hydrocarbons.

212°F
100°C

-4°F
-20°C

50° to 130°F
10° to 54°C

Santoprene® - Injection moulded thermoplastic elastomer with no fabric layer. Long mechanical flex life. Excellent abrasion resistance.

212°F
100°C

-10°F
-23°C

50° to 212°F
10° to 100°C

PTFE - Chemically inert, virtually impervious. Very few chemicals are known to react chemically with PTFE : molten alkali metals, turbulent liquid or gaseous fluorine and a few fluoro-chemicals such as chlorine trifluoride or oxygen difluoride which readily liberate free fluorine at elevated temperatures.

356°F
180°C

32°F
0°C

50° to 212°F
10° to 100°C

Viton® - Shows good resistance to a wide range of oils and solvents : especially all aliphatic, aromatic and halogenated hydrocarbons, acids, animal and vegetable oils. Hot water or aqueous solutions (over 70°F) will attack Viton®.

356°F
180°C

0°F
-18°C

75° to 212°F
24° to 100°C

Polypropylene - High strength, light weight, corrosion resistant polyolefin which easily withstands most chemicals, with no known solvent at room temperature.

158°F
70°C

-40°F
-40°C

50° to 140°F
10° to 60°C

TYPICAL CODE = B50. 05 P T. B B. T T P - T

MODEL

B50 - STANDARD
X50 - ATEX CAT. 2

DESIGN LEVEL

WETTED COMPONENTS

P : POLYPROPYLENE
G : CONDUCTIVE POLY. (ATEX CAT. 2)
K : KYNAR (PVDF)

NON - WETTED COMPONENTS

T : ALUMINIUM / EPOXY PAINTED
W : ST. STEEL / EPOXY PAINTED

VALVE TYPE

B : BALL
W : WEIGHTED BALL

SUCTION ORIENTATION

B : BOTTOM

TAPPED MANIFOLD

VALVE SEATS

B : BUNA-N T : PTFE
E : EPDM V : VITON
N : NEOPRENE
P : POLYPROPYLENE

VALVE BALLS

B : BUNA-N T : PTFE
E : EPDM V : VITON
N : NEOPRENE
S : STAINLESS STEEL

DIAPHRAGMS

B : BUNA-N T : PTFE
E : EPDM V : VITON
H : POLYESTER (HYTREL)
N : NEOPRENE
P : POLYURETHANE
R : SANTOPRENE
O : ONE-PIECE PTFE

IMPORTANT

This pump should be used in accordance with the requirements of the Safety, Health & Welfare at Work Act 2005.
All business conducted subject to IDEX Pump Technologies, Ireland. Terms and Conditions of Sale, available on request.



**BLAGDON
PUMP**

IDEX Pump Technologies (Ireland) Ltd.,
A Unit of IDEX Corporation,
R79, Shannon, Co Clare, IRELAND.
TEL. : +353 61 471933 FAX. : +353 61 475046
Web Site : www.blagdonpump.com
E-Mail : sales@blagdonpump.com